

# Rose Arbor

Quilt designed by Marinda Stewart. Quilt measures approximately 41" x 47"

Fabric	Yardage	Cutting
CX3362 Green	3/4 yard	Cut one piece 22" x 22" centered on rose arbor. Divide the remainder of the panel in half
**CX2932 Gray	1-1/8 yard	See assembly instructions for cutting the arch.
CX2517 Blue	5/8 yard	Cut one piece 18" x 42" wide.
CX2927 Gray	3/8 yard	See assembly instructions for cutting filler pieces.
CX2931 Brown	Fat Quarter	See assembly instructions for cutting path.

45" x 50" fabric for backing

45" x 50" batting

1/6 yard Binding Fabric

## You will also need:

Fusible Web

Threads to Match

Scissors, Straight Pins

Acrylic Ruler, Mat, Rotary Cutter

Rubber Chalk Pencil

Basic Sewing Supplies

OPTIONAL: Non-stick Pressing Sheet

\* One complete repeat is needed. Extra yardage will be used to fussy-cut elements to fill-in areas and diffuse seams.

\*\* Subtle one-way design requires extra yardage.

## Assembly Instructions

- 01) Sew one half panel piece to each side of the center panel. Piece should measure 22" x 42" wide to make the quilt top.
- 02) Sew the 18" x 42" CX2517 Blue piece to the top of the quilt top.
- 03) For rock arch, using a chalk pencil, draw an arch on CX2932. The arch should be 39" high at its peak and approximately 34" wide at its base, with an opening of 20". It should be 6" to 7" thick on the sides. Refer to the photo on the pattern cover.
- 04) Following manufacturer's directions, iron fusible web onto the arch area extending beyond the drawn edges. Fussy-cut around rocks on all sides of the arch. Finished arch should have approximately a 21" wide opening and 6" thick sides. Center the arch over the rose arbor and iron in place on quilt top.
- 05) From the leftover pieces of CX3362 use fusible web and cut out any extra roses. Add to the top of the trellis and either side of the arch to diffuse the seam.
- 06) From CX2931 free-hand cut a path for the foreground, 9" wide at the top, 22" wide at the bottom and 9" tall. Refer to the pattern photo. Sew to the center of the path as in photo. Fill-in any gaps in the pathway with leftover pieces from CX3362 or CX2931.
- 07) From CX2927 rough cut two pieces to fill-in each side of the path. One is approximately 21" wide by 11" tall. The other is approximately 13" wide by 11" tall. Place fusible web on the back along the top edge and pathway edge of each piece. Fussy-cut top and path edge of each piece. Place on top of quilt panel, overlapping the bottom edge of the quilt and the path as shown in photo and iron in place. Trim finished quilt to 42" x 48".
- 08) Layer backing, batting and quilt top. Baste.
- 09) Quilt as desired.
- 10) For binding cut 1" wide strips. Piece as needed. Sew to top and bottom of the quilt. Fold the binding to the back along the seam. Turn under 1/2" as a seam allowance and hand-stitch in place. Binding is visible on the back only. Repeat for each side.

## Disclaimers

- This pattern is provided as a courtesy to quilt stores, catalogs and quilters. Michael Miller Fabrics, LLC is not responsible for the accuracy of any kits packaged to accompany this pattern. Please direct any inquiries to the kit maker.
- Yardage requirements for this pattern may allow for excess yardage to accommodate specific placement of motifs or to allow for any fussy-cutting to achieve the finished quilt design.
- While every attempt has been made to give accurate measurements, yardage requirements and construction directions, this does not allow for personal variations in measuring, cutting and/or sewing. The enclosed directions were used in the construction of the original quilt.