

FABRIC REQUIREMENTS



**DC4044-Blue
Autumn Lake
3/4 yard**



**DC4045-Autumn
Forest Cabins
1/2 yard**



**DC4048-Blue
Deer Lake
Fat 1/4**




**DC4047-Blue
Loons
1/4 yard**



**CX0035-Peri
Sky
3/8 yard**



**CX1087-Sienna
Marble
3/8 yard**



**Jet Brown
3/8 yard**

Backing and Batting - 50" x 54"

Deer Lake



Size: Approximately 45"W x 51"H

Quilt designed by Marinda Stewart
Skill Level: Beginner



118 West 22nd Street 5th Floor New York, NY 10011
Tel: 212.704.0774 Fax: 212. 633. 0272 email: info@michaelmillerfabrics.com

www.michaelmillerfabrics.com

"Deer Lake"

Quilt by Marinda Stewart

Size: Approximately 45"W x 51"H - Skill Level: Beginner

Materials

Fabric	Yardage	Cutting
Sky CX0035 Peri	3/8 yard	(1) 9 1/2" H x 43 1/2" W
Autumn Lake *DC4044 Blue	3/4 yard	(1) 23 1/2" H x 43 1/2" W
Deer Lake DC4048 Blue	Fat 1/4	Fussy cut as shown in quilt photo
Loons DC4047 Blue	1/4 yard	Fussy cut as shown in quilt photo
Forest Cabins DC4045 Autumn	1/2 yard	Fussy cut as shown in quilt photo
Marble CX1087 Sienna	3/8 yard	(4) 1 1/2" x 43 1/2" ** (2) 1 1/2" x 51 1/2"
Jet Brown	3/8 yard	(5) 2 1/4" x W.O.F. binding
* Or amount needed for one complete motif ** Pieced as needed to achieve proper length		
Additional Materials: 1 1/4 yard tearaway stabilizer, 50" x 54" backing, 50" x 54" batting, thread to match, straight pins, scissors, acrylic ruler, rotary cutter, and mat.		

Disclaimers

This pattern is provided as a courtesy to quilt stores, catalogs, and quilters. Michael Miller Fabrics, LLC is not responsible for the accuracy of any kits packaged to accompany this pattern. Please direct any inquiries to the kit maker.

Yardage requirements for this pattern may allow for excess yardage to accommodate specific placement of motifs or to allow for any fussy-cutting to achieve the finished quilt design.

While every attempt has been made to give accurate measurements, yardage requirements, and construction directions; this does not allow personal variations in measuring, cutting, and or sewing. The enclosed directions were used in the construction of the original quilt.

Directions

1. Starting from the top of the quilt, sew one CX1087 43 1/2" strip to the top and bottom of CX0035. Add DC4044 to the bottom of the quilt. Sew another CX1087 43 1/2" strip to the bottom edge of DC4044. Set aside.
2. For the bottom panel, refer to the quilt photo for placement. Use tear-away stabilizer cut to 15 1/2" x 43 1/2" as the background template for the finished panel. Cover the stabilizer completely with the appliqued fabrics. Fussy cut DC4047 as shown. Place on top of the stabilizer at the top and to the right. Pin in place to hold. Fussy cut deer from DC4048. Add to the top left of the panel overlapping the raw edges of DC4047. Machine applique in place. Fussy cut a tree top edge across the width of DC4045 as shown. Place face up on top of the raw edges of DC4047 and DC4048. Machine applique in place. Remove tearaway stabilizer and any excess fabric carefully from the back of the panel. Trim panel to measure 15 1/2" H x 43 1/2" W. Sew to the bottom of the quilt.
3. Sew remaining CX1087 43 1/2" strip to the bottom of the quilt.
4. Sew one CX1087 51 1/2" strip to each side of the quilt.
5. Layer backing, batting, and quilt top. Baste.
6. Quilt as desired.
7. Bind quilt using Jet Brown to finish.