

Dick and Jane

Quilt designed by Marinda Stewart. Finished quilt size approximately 50" x 50"

Fabric Requirements:

3/4 yard of DJ3157 Cream
3/4 yard of DJ3151 Retro
1/6 yard of CX0940 Red
3/8 yard of DJ3153 Primary
1/6 yard CX3138 Cream
3/4 yard of CX3136 Black
5/8 yard of CX3137 Red
5/8 yard of DJ3216 Cream
1/4 yard of DJ3154 Cream
56" square for backing
56" square piece of batting
Acrylic ruler, mat and rotary cutter
100% cotton thread
Basic sewing supplies

Cutting Instructions:

Cut nine 2-1/2" x width of fabric (WOF) strips.
Cut the strips into eighty-one 2-1/2" x 4-1/2" strips.
Cut nine 2-1/2" x width of fabric (WOF) strips.
Cut the strips into eighty-one 2-1/2" x 4-1/2" strips.
Cut two 1" x 37-1/2" strips and two 1" x 36-1/2" strips.
Fussy cut two 1-1/2" x 39-1/2" strips and two 1-1/2" x 37-1/2" strips, centering the square pattern on the strip.
Cut two 1" x 40-1/2" strips and two 1" x 39-1/2" strips.
Cut two 1-1/4" x 42" strips and two 1-1/4" x 40-1/2" strips. Cut five 1" x WOF strips. Cut five 2-1/4" x WOF strips and piece them together for the binding.
Cut four 5" x 42" strips.
Fussy cut four 5" squares centering a motif in each.
See directions for Tossed Applique Blocks.
See directions for Tossed Applique Blocks.

Disclaimers

1. This pattern is provided as a courtesy to quilt stores, catalogs and quilters. Michael Miller Fabrics, LLC is not responsible for the accuracy of any kits packaged to accompany this pattern. Please direct any inquiries to the kit maker.
2. Yardage requirements for this pattern may allow for excess yardage to accommodate specific placement of motifs or to allow for any fussy-cutting to achieve the finished quilt design.
3. While every attempt has been made to give accurate measurements, yardage requirements and construction directions, this does not allow for personal variations in measuring, cutting and/or sewing. The enclosed directions were used in the construction of the original quilt.

Assembly Instructions:

1. Sew one 2-1/2" x 4-1/2" DJ3157 to top of one 2-1/2" x 4-1/2" DJ3151 to make one 4-1/2" square block. Repeat to make eighty-one blocks.
2. To assemble the quilt background sew nine blocks together in one row alternating the placement of each block horizontally and vertically. Make five identical rows. Make four rows alternating the placement of the blocks.
3. Sew the rows together alternating the rows to create a stair step pattern across the quilt top.
4. Sew one 1" x 36-1/2" CX0940 strip to the top and bottom of the quilt top. Sew one 1" x 37-1/2" CX0940 strip to the side of the quilt top.
5. Sew one 1-1/2" x 37-1/2" DJ3153 strip to the top and bottom of the quilt top. Sew one 1-1/2" x 39-1/2" DJ3153 strip to each side of the quilt top.
6. Sew one 1" x 39-1/2" CX3138 to the top and bottom of the quilt top. Sew one 1" x 40-1/2" CX3138 to each side of the quilt top.
7. Sew one 1-1/4" x 40-1/2" strip to the top and bottom of the quilt top. Sew one 1-1/4" x 42" strip to each side of the quilt top.
8. Sew one 5" x 42" CX3137 strip to top and bottom of the quilt top.
9. Sew one 5" DJ3216 square to each end of the remaining two 4" x 42" CX3137 strips. Sew the strip to each side of the quilt top.
10. For the tossed blocks- fussy cut a total of thirteen assorted rectangles of your choice from DJ3216 and DJ3154.
11. Take the five 1" x WOF strips of CX3136 and border all four sides of each rectangle cut in Step 10. Cut more strips if necessary.
12. Turn under a 1/4" seam allowance on all four sides of each motif block and press in place.
13. Arrange the motif blocks randomly across the quilt top. Top stitch each block in place.
14. Carefully cut away the background quilt top from behind each motif block leaving 1/4" seam allowance.
15. Layer quilt and bind as desired.