CHISHOLM TRAIL



FABRIC REQUIREMENTS

54" X 70" BATTING 54" X 70" BACKING: IF NOT MAKING THE QUILT REVERSIBLE



CX6761 Brick Spearhead Stripe 1 1/2 yards



CX6760 Brick Marshall 3/4 yard



CX6761 Brown Spearhead Stripe 1 1/2 yards Optional Backing



CX6759 Brick Flint 1/8 yard



CX6758 Brick Arrowhead 1/2 yard



CX6757 Denim Maddox 1/4 yard



CX6756 Brown Lasso Stripe 1 1/2 yards Optional Backing



CX6935 Denim **Travis** 1 yard

Chisolm Trail

Quilt by Marinda Stewart | Skill Level: Confident Beginner | Size: 48" W x 65" H

This quilt is an example of making the fabric do all of the work. It has only twelve (12) seams. It is important to pay attention to the fabric motif when cutting out the panels of fabric.

OPTIONAL: The quilt can be made reversible by using the two different coordinating fabrics on the back.

Fabric	Yardage	Cutting
CX6761 Brick	1 1/2 yards	(2) 12" x 42 1/4" *
Spearhead Stripe		(2) 8 1/2" x 48 1/2" *
CX6935 Denim	1 yard	(1) 11 3/4" x 42 1/4" *
Travis		(2) 4" x 42 1/4" *
CX6760 Brick	3/4 yard	(2) 3 1/2" x 48 1/2" **
Marshall		
CX6758 Brick	1/2 yard	(6) 2 1/2" x W.O.F. – binding
Arrowhead		
CX6757 Denim	1/4 yard	(2) 3" x 42 1/4" – center on
Maddox		motif
CX6759 Brick	1/8 yard	(2) 1 1/2" x 42 1/4"
Flint		
OPTIONAL: Backing	1 1/2 yards	(1) 12" x 54"
CX6761 Brown		(1) 18" x 54"
Spearhead Stripe		
OPTIONAL: Backing	1 1/2 yards	(1) 42" x 54"
CX6756 Brown		
Lasso Stripe		

Also Needed: 54" x 70" batting, (54" x 70" backing - if not making the quilt reversible), scissors, straight pins, thread to match, acrylic ruler, rotary cutter, and mat.

^{*} Cut two identical pieces from the same area of the fabric. They will mirror image each other in the quilt.

^{**} This fabric is cut vertically, centered on the motif and pieced for length.

Disclaimers

This pattern is provided as a courtesy to quilt stores, catalogs, and quilters. Michael Miller Fabrics, LLC is not responsible for the accuracy of any kits packaged to accompany this pattern. Please direct any inquiries to the kit maker. Yardage requirements for this pattern may allow for excess yardage to accommodate specific placement of motifs or to allow for any fussy-cutting to achieve the finished quilt design. While every attempt has been made to give accurate measurements, yardage requirements, and construction directions; this does not allow personal variations in measuring, cutting, and or sewing. The enclosed directions were used in the construction of the original quilt.

Directions:

- 1. Sew one CX671 Brick 12" x 42 1/4" piece to each side of CX6935 11 3/4" x 42 1/4" piece. Sew one CX6935 4" x 42 1/4" piece to each outside edge. Sew one CX6759 1 1/2" x 42 1/4" piece to each outside edge. Sew one CX6757 3" x 42 1/4" to each outside edge to make one 4 1/4" H x 48 1/2" W piece.
- 2. Sew one CX6760 3 1/2" x 48 1/2" strip, pieced for length to the top and bottom of the quilt. Sew one CX6761 Brick 8 1/2" x 48 1/2" strip to the top and bottom of the quilt.
- 3. OPTIONAL Reversible Backing sew one CX6761 Brown 12" x 54" piece to the top edge of the CX6756 42" x 54" piece. Sew one CX6761 Brown 18" x 54" piece to the bottom.
- **4.** Layer backing, batting, and quilt top. Baste.
- **5.** Quilt as desired. (Note:) The patterns in the quilt top were used for the quilting pattern.
- **6.** Bind quilt using CX6758 2 1/2" strips pieced as needed for length.