


- Free Store Model with Purchase as Shown on Cover -

Get a Free Store Model 58" x 58" strip quilt featuring Arrows Southwest with an order of a casepack (the entire collection is 7 skus). All bolt sizes are 12 yards.

Free Store Display - use style #GWP0025



**SMD7581 Mango
Minky Dots**



**SMD7581 Turquoise
Minky Dots**



**SMS7580 Bright Purple
Slinky Minky**



**SMS7580 Orange
Slinky Minky**



**SMZ7698 Gray
Arrows**



**SMZ7698 White
Arrows**



**VS7584 Turquoise
Velvet Snuggle**

Arrows Southwest Strip Quilt 58" x 58"

Yardages based on fabric 58"-60" wide.

| | | | |
|----------|------------------------|---------------------------|-------------|
| Fabric A | SMZ7698-White | Arrows-White | 5/8 yard |
| Fabric B | SMD7581-Mango | Minky Dots-Mango | 5/8 yard |
| Fabric C | SMZ7698-Gray | Arrows-Gray | 7/8 yard |
| Fabric D | SMS7580-Orange | Silky Minky-Orange | 1/3 yard |
| Fabric E | SMS7580-Bright Purple* | Silky Minky-Bright Purple | 1/3 yard |
| Backing | Your Choice | | 1-3/4 yards |

*includes Binding

Cutting:

Fabric A, cut:

- (1) 10 ½" x width of fabric (WOF) strip.
- (2) 3 ½" x WOF strips

Fabric B, cut:

- (1) 10 ½" x WOF strip
- (2) 3 ½" x WOF strips

Fabric C, cut:

- (2) 10 ½" x WOF strips
- (1) 3 ½" x WOF strip

Fabric D, cut:

- (3) 3 ½" x WOF strips

Fabric E, cut:

- (5) 2" x WOF strips for the binding

Backing, cut:

- (1) 60" x 60"

You will also need:

- 60x60 backing
- 58x58 batting (if desired)
- Spray adhesive (505)
- Flower head pins
- Walking Foot (recommended)

Sewing and Basic Technique for Sewing Strip Quilts:

This quilt is sewn using the flip and sew method. Each strip is sewn on the foundation of the quilt, sewing through all layers, backing and batting. This means the quilt is quilted when you are done!

1. Lay the backing fabric on a flat surface. Place the batting centered exactly on top of the backing. Spray fusible adhesive to hold batting to backing fabric.
2. Smooth out all wrinkles. Fold in half keeping the 60" wide horizontal. Mark the center of the backing and batting piece.
3. You will start with the fourth strip for this version. Lay the fourth strip on the batting, aligning the top edge with the marked line on the batting. Use spray adhesive to secure in place.
4. Choose your next strip and pin in place with right sides together, lining up the raw edges along one horizontal side. Use a 1/2" seam allowance to attach the strips to the batting and backing. You will be sewing through the strip you pinned, the center strip, the batting and the backing.
5. Smooth the strip right side up and spray to secure in place. Repeat step 4 on the other side of the middle strip.
6. Continue to sew strips alternating sides working from the middle. Repeat pinning and sewing until all strips are sewn. Baste the outer edge down before you attach binding. Trim all edges to even up.
7. Bind with 2" strips sewn together.

