

SIZE: 72  $\frac{3}{4}$ " x 73" • LEVEL: ADVANCED • PATTERN BY: NATALIE CRABTREE • MARINE METALLIC BATIKS COLLECTION PATTERN AVAILABLE ON: WWW.MICHAELMILLERFABRICS.COM



THIS IS A DIGITAL REPRESENTATION OF THE QUILT TOP, FABRIC MAY VARY.





FABRIC A
BTM9205
Bermuda Triangle Cream
2 1/8 yards
(includes binding)



FABRIC B BTM9198 Sand Gems Sangria 3% yard



FABRIC C BTM9202 Turtle Island Sunset ½ yard




FABRIC D BTM9198 Sand Gems Flamingo ½ yard



FABRIC E BTM9199 Coral Reef Fire ½ yard



FABRIC F BTM9199 Coral Reef Mango ½ yard



FABRIC G BTM9199 Coral Reef Wave ½ yard



FABRIC H BTM9198 Sand Gems Stream ½ yard




FABRIC I BTM9198 Sand Gems Riviera ½ yard



FABRIC J BTM9200 Sea Creature Topaz ½ yard



FABRIC K
BTM9205
Bermuda Triangle Garnet
½ yard



FABRIC L BTM9199 Coral Reef Quartz 3% yard



FABRIC M BTM9198 Sand Gems Marine 1 1/8 yards



### Additional supplies needed:

Batting: 79" x 80 1/2" piece of batting for approximately 3" overage on each side

Backing: 4 ½ yards

Basic sewing tools, Template plastic optional but recommended

KEY	CUTTING INTRUCTIONS
A	<ul> <li>Cut (8) 2 ¼" x WOF strips for Border 1. Sew (2) WOF strips together using a diagonal seam. Repeat (4) times. Trim seams to ¼". Subcut the following (Please note: Border measurements are approximate due to the quilt's diagonal setting. For more accuracy, measure the trimmed quilt top center after completion, and base border measurements from the actual quilt measurements.): <ul> <li>(2) 2" x 65 ½" strips for Border 1 sides.</li> <li>(2) 2" x 68 ¼" strips for Border 1 top/bottom.</li> </ul> </li> <li>Cut (28) 2 1/8" x WOF strips. Unfold WOF strips before cutting. You may layer strips one on top of another to cut multiple at once, however strips should be right sides up. Subcut: <ul> <li>(70) Template D</li> <li>(70) Template E</li> </ul> </li> </ul>
В	• Cut (2) 5 ½" x WOF strips. Subcut (8) Template B from the strips. Turn the templates 180° after each cut to best utilize fabric.
С	• Cut (2) 6 ¼" x WOF strips. Subcut (7) Template A from the strips.
D	• Cut (2) 6 1/4" x WOF strips. Subcut (8) Template A from the strips.
E	• Cut (2) 6 1/4" x WOF strips. Subcut (7) Template A from the strips.
F	• Cut (2) 6 ¼" x WOF strips. Subcut (8) Template A from the strips.
G	• Cut (2) 6 ¼" x WOF strips. Subcut (7) Template A from the strips.
Н	• Cut (2) 6 ¼" x WOF strips. Subcut (8) Template A from the strips.
ı	• Cut (2) 6 1/4" x WOF strips. Subcut (7) Template A from the strips.
J	• Cut (2) 6 ¼" x WOF strips. Subcut (8) Template A from the strips.
K	• Cut (2) 6 ¼" x WOF strips. Subcut (7) Template A from the strips.
L	• Cut (2) 5 ½" x WOF strips. Subcut (8) Template B from the strips. Turn the templates 180° after each cut to best utilize fabric.



М

- Cut (8) 3" x WOF stirps for Border 2. Sew (2) WOF strips together using a diagonal seam. Repeat (4) times. Trim seams to ¼". Subcut the following (Please note: Border measurements are approximate due to the quilt's diagonal setting. For more accuracy, measure the trimmed quilt top center after completion, and base border measurements from the actual quilt measurements.):
  - o (2) 3" x 68 1/2" strips for Border 2 sides.
  - o (2) 3" x 73 ¼" strips for Border 2 top/bottom.
- Cut (6) 2 1/8" x WOF strips. Subcut (82) Template C.


#### **Quilt Assembly:**

- 1. Begin sashing assembly for the quilt by laying out Fabric A Template D sashing pieces and Fabric M Template C corner diamond pieces as shown. Templates C and D will be sewn together diagonally. There should be a ¼" point (dog ear) present at the top and bottom of the unit while sewing as shown. (For example, pictured is a ¼" of excess Fabric A at the top of the unit while sewing. There is a ¼" of excess Fabric M at the bottom of the unit while sewing.)
- 2. Begin the seam where the two fabrics intersect, which will be a ¼" away from the side of the unit.
- 3. Use these template piecing methods to complete sashing strips. When piecing sashing strips, press all seams toward Fabric A.











- 4. Use the sashing assembly instructions provided above to assemble the following quantity of sashing strips varying in length. For all sashing strips begin and end the strip with a Fabric M Template C corner stone.
  - a. Create (2): Use (2) Fabric M Template C & (1) Fabric A Template D
  - b. Create (2): Use (4) Fabric M Template C & (3) Fabric A Template D
  - c. Create (2): Use (6) Fabric M Template C & (5) Fabric A Template D
  - d. Create (2): Use (8) Fabric M Template C & (7) Fabric A Template D
  - e. Create (2): Use (10) Fabric M Template C & (9) Fabric A Template D
  - f. Create (2): Use (11) Fabric M Template C & (10) Fabric A Template D







- 5. Lay out Template A and Template B pieces cut from Fabrics B-L as shown. Template A pieces will be placed in alphabetical order beginning at the top row and ending at the bottom row. Place (1) Fabric A Template E piece in between each Template A piece. Place sashing strips in between each diagonal Template A row as shown.
- 6. Template A & B pieces will be sewn to Template E pieces using the same piecing instructions provided for the sashing strips. See diagram for reference. Sew diagonal Template A rows, pressing all seams toward Template E.







- 7. Once Template A rows are pieced, begin sewing Template A rows and sashing strips together diagonally as shown. Align Template A rows and sashing strips using the corner stones and Template D and E pieces as the guide. Please note that Template B pieces should create the top and bottom rows of the quilt top center. Use pins to keep seams aligned as shown.
- 8. Repeat Template A row and sashing strip methods until all rows and strips have been sewn together for a completed quilt top center.
- 9. Trim excess Template A, B and C fabric along the perimeter of the quilt top even with the sashing strips as shown.








10. Attach Fabric A Border 1 and Fabric M Border 2 prepared during cutting instructions in numerical order. For all borders, sew the side borders on first followed by the top/bottom borders. Press all seams outward toward the last sewn border to complete the quilt top. Quilt top should measure 73 1/4" x 73 1/2" unfinished.






### Finishing the Quilt:

- 11. Sandwich quilt top with batting and backing. Baste quilt layers together using your preferred method.
- 12. Quilt as desired.
- 13. Bind quilt using your preferred method with (8) Fabric A 2 ¼" x WOF strips. Enjoy!








### Mermaid's Tail

**Templates** 



1 Inch